

Safety Data Sheet

Issue Date 11/20/2006



SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name Sure Seal 100 Concrete Sealer

Other means of identification

SDS # / Grade CP- 1544

Recommended Use of the Chemical and Restrictions on Use

Relevant identified use(s) - Sealing and protecting concrete and aggregate surfaces.

Details of the Supplier of the Safety Data Sheet

Supplier Perk Products & Chemical Co.
42 Industry Street
Nashville, TN 37210
www.Perk-Products.com

Emergency telephone number

Company Phone: (615) 242-6157

Emergency Phone: (800) 424-9300 – CHEMTREC

SECTION 2: HAZARDS IDENTIFICATION

Classification

| | |
|---|--------------------|
| Skin Corrosion / Irritation | Category 2 |
| Serious Eye Damage / Eye Irritation | Category 2 |
| Germ Cell Mutagenicity | Category 1B |
| Carcinogenicity | Category 1B |
| Specific target organ toxicity (single exposure) | Category 3 |
| Aspiration Toxicity | Category 1 |
| Flammable Liquids | Category 3 |

Signal Word

DANGER

Hazard Statements

Causes Skin Irritation
Causes serious eye irritation
Carcinogenic
May cause respiratory irritation. May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Flammable liquid and vapor



Appearance: Clear, colorless liquid

Physical State: Liquid

Odor: Moderate aromatic

Precautionary Statements - Prevention

Obtain special instructions before use; do not use until all safety precautions have been read and understood

Use personal protective equipment as required

Product is combustible

Do not ingest

Wear eye/face protection

Wash skin thoroughly with soap and water

Avoid contact with eyes and prolonged contact with skin

Vapors harmful, avoid breathing of vapor or mist

Use in well ventilated areas

Keep away from heat/open flame/other heat sources. –No smoking

Keep container closed tightly

Ground/bond container and receiving equipment

Use explosion-proof equipment

Use only non-sparking tools

Take precautionary measures against static spark

Keep cool

Precautionary Statements - Response

If exposed or concerned: Seek medical advice/attention

IF IN EYES: Flush with clean water for at least 10-15 minutes. Call a physician.

IF ON SKIN: Wash thoroughly with soap and water. If irritation develops, seek medical attention.

IF INDUCED INTERNALLY: Do not induce vomiting. Call a physician or poison control center immediately.

IF INHALED: Move to fresh air and avoid breathing fumes. Contact a physician if breathing becomes difficult.

Precautionary Statements – Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements – Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards Not Otherwise Classified (HNOC)

May be harmful in contact with skin

Other Hazards

Toxic to aquatic life with long lasting effects

Toxic to aquatic life

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

| Chemical Name | CAS No | Weight-% |
|---|------------|----------|
| Copolymer of Styrene and 2-Ethylhexylacrylate | 25153-46-2 | <50 |
| Petroleum naphtha, light aromatic | 64742-95-6 | <50 |
| 1,2,4 Trimethylbenzene | 95-63-6 | 5-25 |
| 1,3,5 Trimethylbenzene | 108-67-8 | 0-6 |
| Xylene | 1330-20-7 | 0-2 |
| Cumene | 98-82-8 | 0-2 |
| Styrene | 100-42-5 | 0-1 |
| | | |

SECTION 4: FIRST AID MEASURES

First Aid Measures

| | |
|-----------------------|--|
| General Advice | If exposed or concerned: Get medical advice/attention |
| Eye Contact | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation occurs. |
| Skin Contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse. Get medical attention if irritation develops or persists. |
| Inhalation | Remove to fresh air. If not breathing, give artificial respiration. Get medical attention immediately. |
| Ingestion | DO NOT induce vomiting because of danger of aspirating liquid into lungs. If spontaneous vomiting occurs, keep head below hips to prevent aspiration and monitor breathing. Call a physician or poison control center immediately. |

Most Important Symptoms and Effects, both Acute and Delayed

| | |
|-----------------|--|
| Symptoms | May cause dermatitis or irritation in some individuals upon prolonged contact. Eyes may have symptoms of redness, itching, irritation and watering from overexposure. Aspiration hazard: if swallowed can enter lungs and cause damage. May cause irritation to the mucous membranes and upper respiratory tract. Prolonged breathing of vapors may cause nausea, headache, weakness and/or dizziness. |
|-----------------|--|

Indication of any Immediate Medical Attention and Special Treatment Needed

| | |
|---------------------------|-----------------------|
| Note to Physicians | Treat symptomatically |
|---------------------------|-----------------------|

SECTION 5: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray (fog). Dry chemical. Alcohol resistant foam. AFFF. Carbon dioxide (CO₂)

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Cool surrounding equipment, fire-exposed containers, and structures with water. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products Carbon monoxide. Carbon dioxide (CO₂). Reactive hydrocarbons. Irritating vapors.

Sensitivity to Mechanical Impact Sensitive to shock.

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

| | |
|----------------------------------|---|
| Personal Precautions | Use personal protective equipment as required. Remove all sources of ignition. Avoid breathing vapors. Ventilate affected area. |
| Environmental Precautions | See Section 12 for additional ecological information |

Methods and Material for Containment and Cleaning Up

| | |
|--------------------------------|---|
| Methods for Containment | Prevent further leakage or spillage if safe to do so. |
| Methods for Cleaning Up | Absorb spillage with non-combustible, absorbent material. Clean up in accordance with all applicable regulations. |

SECTION 7: HANDLING AND STORAGE**Precautions for Safe Handling**

| | |
|--------------------------------|--|
| Advice on Safe Handling | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection recommended in Section 8. Wash face, hands, and any exposed skin thoroughly after handling. Avoid breathing vapors or mists. Use only with adequate ventilation. Keep away from heat/sparks/open flames/hot surfaces. –No smoking. |
|--------------------------------|--|

Conditions for Safe Storage, Including any Incompatibilities

| | |
|-------------------------------|---|
| Storage Conditions | Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. |
| Packing Materials | Do not transfer to unmarked containers. |
| Incompatible Materials | Strong oxidizing agents. |

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION**Exposure Guidelines**

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|------------------------------------|-----------------------------|---|---|
| 1,2,4 Trimethylbenzene 95-63-6 | - | - | TWA: 25ppm TWA: 125 mg/m ³ |
| 1,3,5 Trimethylbenzene 108-67-8 | - | - | TWA: 25ppm TWA: 125 mg/m ³ |
| Xylene 1330-20-7 | STEL: 150ppm TWA: 100ppm | TWA: 100ppm TWA: 435 mg/m ³ (vacated) TWA: 100ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150ppm (vacated) STEL: 655 mg/m ³ | - |
| Cumene 98-82-8 | TWA: 50ppm | TWA: 50ppm TWA: 245 mg/m ³ (vacated) TWA: 50ppm (vacated) TWA: 245 mg/m ³ (vacated) S* S* | IDLH: 900ppm TWA: 50ppm TWA: 245mg/ m ³ |
| Styrene 100-42-5 | STEL: 40ppm TWA: 20ppm | TWA: 100ppm (vacated) TWA: 50ppm (vacated) TWA: 215 mg/m ³ (vacated) STEL: 100ppm (vacated) STEL: 425 mg/m ³ Ceiling: 200ppm | IDLH: 700ppm TWA: 50ppm TWA: 215mg/m ³ STEL: 100ppm STEL: 425mg/m ³ |

Appropriate Engineering Controls

| | |
|-----------------------------|---|
| Engineering Controls | Apply technical measures to comply with the occupational exposure limits. Eyewash stations. |
|-----------------------------|---|

Individual Protection Measures, such as Personal Protective Equipment

| | |
|---------------------------------|--|
| Eye/Face Protection | Wear approved safety goggles |
| Skin and Body Protection | Chemical resistant, impermeable gloves. Use protective clothing chemically resistant to this material. |

Respiratory Protection

Ensure adequate ventilation, especially in confined areas. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES
Information on Basic Physical and Chemical Properties

| | | | |
|-----------------------|-------------------------|-----------------------|-------------------|
| Physical State | Liquid | Odor | Moderate aromatic |
| Appearance | Clear, colorless liquid | Odor Threshold | Not determined |
| Color | Colorless | | |

| <u>Property</u> | <u>Values</u> | <u>Remarks °Method</u> |
|-------------------------------------|-------------------------|-------------------------------|
| pH | Not Determined | |
| Melting Point/Freezing Point | Not Determined | |
| Boiling Point/Boiling Range | 160-174 °C / 320-345 °F | |
| Flash Point | 37-46 °C / 100-115 °F | Tag Closed Cup |
| Evaporation Rate | 0.1 | (butyl acetate = 1) @ 25°C |
| Flammability (Solid, Gas) | n/a liquid | |
| Upper Flammability Limits | Unknown | |
| Lower Flammability Limit | 1% (approximate) | |
| Vapor Pressure | <10 mm Hg | @ 25°C (77°F) |
| Vapor Density | 3.5 | (Air=1) |
| Specific Gravity | 0.95 | (1=Water) @ 15°C |
| Water Solubility | Negligible | |
| Solubility in Other Solvents | Not Determined | |
| Partition Coefficient | Not Determined | |
| Autoignition Temperature | 471 °C / 880 °F | |
| Decomposition Temperature | Not Determined | |
| Kinematic Viscosity | Not Determined | |
| Dynamic Viscosity | Not Determined | |
| Explosive Properties | Not Determined | |
| Oxidizing Properties | Not Determined | |

SECTION 10: STABILITY AND REACTIVITY
Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to Avoid

Avoid heat, sparks, open flames and other ignition sources.

Incompatible Materials Strong Oxidizing Agents.

Hazardous Decomposition Products

Carbon Monoxide.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Product Information

| | |
|---------------------|--|
| Eye Contact | Causes serious eye irritation |
| Skin Contact | Causes skin irritation. May be harmful in contact with skin. |
| Inhalation | Avoid breathing vapors or mists. |
| Ingestion | Do not taste or swallow. |

Component Information

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---|-------------------|----------------------|---|
| Petroleum naphtha, light aromatic 64742-95-6 | =8400 mg/kg (Rat) | >2000 mg/kg (Rabbit) | >5.2 mg/L (Rat) 4 h = 3400ppm (Rat) |
| 1,2,4 Trimethylbenzene 95-63-6 | =3400 mg/kg (Rat) | >3160 mg/kg (Rabbit) | = 18 g/m ³ (Rat) 4 h |
| 1,3,5 Trimethylbenzene 108-67-8 | =5000 mg/kg (Rat) | - | = 24 g/m ³ (Rat) 4 h |
| Xylene 1330-20-7 | =4300 mg/kg (Rat) | >1700 mg/kg (Rabbit) | = 5000ppm (Rat) 4 h = 47635 Mg/L (Rat) 4 h |
| Cumene 98-82-8 | =1400 mg/kg (Rat) | >3160 mg/kg (Rabbit) | =39000 mg/m ³ (Rat) 4 h |
| Styrene 100-42-5 | =1000 mg/kg (Rat) | - | =11.8 mg/L (Rat) 4 h |

Information on Physical, Chemical and Toxicological Effects

Symptoms Please see section 4 of this SDS for symptoms

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Germ Cell Mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

| Chemical Name | ACHIH | IARC | NTP | OSHA |
|---------------------|-------|----------|------------------------|------|
| Xylene 1330-20-7 | | Group 3 | | |
| Cumene 98-82-8 | | Group 2B | | X |
| Styrene 100-42-5 | | Group 2B | Reasonably Anticipated | X |

Legend

IARC (International Agency for Research on Cancer)

Group 2B – Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

NTP (National Toxicology Program)

Reasonably Anticipated – Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

STOT – Single Exposure May cause respiratory irritation. May cause drowsiness or dizziness.

Aspiration Hazard May be fatal if swallowed and enters airways.

Numerical Measures of Toxicity

Not determined

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic organisms. Toxic to aquatic life with long lasting effects.

| Chemical Name | Algae/aquatic plants | Fish | Toxicity to Microorganisms | Crustacea |
|---|--|--|--|--|
| Petroleum naphtha, light aromatic 64742-95-6 | | 9.22: 96 h Oncorhynchus Mykiss mg/L LC50 | | 6.14: 48 h Daphnia magna mg/L LC50 |
| 1,2,4 Trimethylbenzene 95-63-6 | | 7.19-8.28: 96 h Pimephales promelas mg/L LC50 flow-through | | 6.14: 48 h Daphnia magna mg/L LC50 |
| 1,3,5- Trimethylbenzene 108-67-8 | | 3.48: 96 h Pimephales Promelas mg/L LC50 | | 50: 24 h Daphnia magna mg/L LC50 |
| Xylene 1330-20-7 | | 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 – 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 – 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 – 16.5: 96 h lepomis macrochirus mg/L LC50 flow-through 19:96 h lepomis macrochirus mg/L LC50 7.711-9.591: 96 h lepomis macrochirus mg/L LC50 static 23.53 – 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h cyprinus carpio mg/L LC50 30.26 – 40.75: 96 h Poecilia reticulate mg/L LC50 static | EC50 = 0.0084 mg/L 24 h | 3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus Lacustris mg/L LC50 |
| Cumene 98-82-8 | 2.6: 72 h Pseudokirchneriella Subcapitata mg/L EC50 | 6.04-6.61: 96h h Pimephales promelas mg/L LC50 flow-through 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 5.1: 96 h Poecilia reticulate mg/L LC50 semi-static | EC50 = 0.89 mg/L 5 min EC50 = 1.10 mg/L 15 min EC50 = 1.48 mg/L 30 min EC50 = 172 mg/L 24 h | 0.6:48 h Daphnia magna Mg/L EC50 7.9 – 14.1: 48 h Daphnia magna mg/L EC50 Static |
| Styrene 100-42-5 | 1.4: 72 h Pseudokirchneriella Subcapitata mg/L EC50 0.72: 96 h h Pseudokirchneriella Subcapitata mg/L EC50 0.46 - 4.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 0.15 – 3.2: 96 h Pseudokirchneriella subcapitata mg/L EC50 static | 3.24-4.99: 96 h Pimephales promelas mg/L LC50 flow-through 19.03-33.53: 96 h Lepomis macrochirus mg/L LC 50 static 6.75-14.5: 96 h Pimephals promelas mg/L LC50 static 58.75-95.32: 96 h Poecilia Reticulate mg/L LC50 static | EC50 = 5.4 mg/L 5 min | 3.3 – 7.4: 48 h Daphnia magna mg/L LC50 |

Persistence and Degradability

Not determined

Bioaccumulation

Not determined

Mobility

| Chemical Name | Partition Coefficient |
|-----------------------------------|-----------------------|
| 1,2,4 Trimethylbenzene 95-63-6 | 3.63 |
| Xylene 1330-20-7 | 2.77 – 3.15 |
| Cumene 98-82-8 | 3.55 |
| Styrene 100-42-5 | 2.95 |

Other Adverse Effects

Not determined

SECTION 13: DISPOSAL CONSIDERATIONS**Waste Treatment Methods**

Disposal of Waste Do not throw used container in fire. Disposal should be in accordance with local/state/national regulations.

Contaminated Packaging Do not throw used container in fire. Disposal should be in accordance with local/state/national regulations.

| Chemical Name | RCRA | RCRA – Basis for Listing | RCRA – D Series Wastes | RCRA – U Series Wastes |
|---------------------|------|-----------------------------------|------------------------|------------------------|
| Xylene 1330-20-7 | | Included in waste stream: F039 | | U239 |
| Cumene 98-82-8 | | | | U055 |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste Status |
|---------------------|-----------------------------------|
| Xylene 1330-20-7 | Toxic Ignitable |
| Cumene 98-82-8 | Toxic Ignitable |
| Styrene 100-42-5 | Toxic Ignitable |

SECTION 14: TRANSPORTATION INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances. This may be non-regulated in non-bulk packages for DOT ground only per 49 CFR 173.150(f)

DOT

UN/ID No UN1993
Proper Shipping Name Flammable liquid, n.o.s (Light aromatic petroleum naphtha)
Hazard Class 3
Packing Group III

IATA

UN/ID No UN1993
Proper Shipping Name Flammable liquid, n.o.s (Light aromatic petroleum naphtha)
Hazard Class 3
Packing Group III

IMDG

UN/ID No UN1993
Proper Shipping Name Flammable liquid, n.o.s (Light aromatic petroleum naphtha)
Hazard Class 3
Packing Group III

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|--------------------------------------|-------------------|----------------------|---------------------|
| Xylene 1330-20-7 | X | X | X |
| Cumene 98-82-8 | | X | |
| Styrene 100-42-5 | X | X | X |
| 1,2,4 Trimethylbenzene 95-63-6 | X | X | X |
| 1,2,5 – Trimethylbenzene 108-67-8 | X | X | X |

SECTION 16: OTHER INFORMATION

| | | | | |
|--------------------|----------------------------|--------------------------|-------------------------|--|
| <u>NFPA</u> | Health Hazards 2 | Flammability 2 | Instability 0 | Special Hazards Not determined |
| <u>HMIS</u> | Health Hazards 2 | Flammability 2 | Instability 0 | Personal Protection Not determined |

Issue Date 16-Aug-2002
Last Revision Date 22-April-2015

Disclaimer/Statement of Liability:

The information in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Perk Products Co. makes no warranty expressed or implied concerning this material except that it conforms to the description of this SDS. Neither Perk Products & Chemical Co, Inc., nor the seller shall be held responsible in any manner for personal injury or property damage, or other types of loss resulting from the handling, storage, or use of this product. The buyer assumes all risk.

End of Safety Data Sheet